



ZeroSmog Guard Light Kit1 ALFA 120 V

Item No: FT91024299 ZeroSmog Guard Light - Single User Entry Level Filtration Unit Kit with Accessories 60 W, 120 V

ZeroSmog Guard Light, 120 V, 1 x main filter (HEPA H13 and Activated Carbon) 5 x ePM1-75% prefilters 1 x ALFA nozzle, 1 x 0F15 Hose 1 x Desk clamp

KEY FEATURES

Highest level filtration – for cleaner and healthier air
 High efficiency particle and gas filtration
 Odour removal during soldering
 Powerful blower maintains suction pressure throughout the filter's life
 High flow rate to collect all the smoke
 Quiet - lowest noise level on the market – less than 50dB
 Easy main and pre-filter change
 Low maintenance
 Easy-to-reach on/off switch
 ESD safe
 Retains Weller Easy-Click 60 Hose system

🕒 Clean & Healthy Air

Provides superior air quality through high-efficiency filtration of soldering particles and gases with a large filtering surface (H13 HEPA particle filter, activated carbon).

Superior Experience Lowest noise level on the market ensures a healthy, pleasant, and comfortable working environment.

- Quick and Easy Filter Change
 Ensures user convenience with fast, hassle-free replacements of both, prefilter and main filter.
- Compact Design
 Saves space with a compact, under-the-bench design ideal for single-user use.
- Powerful Extraction

The robust blower maintains sufficient suction pressure throughout the filter's life, ensuring a high flow rate to capture all smoke effectively.

 Single User Entry Level Filtration Unit Kit with Accessories 60 W, 120 V
 Highest level filtration – for cleaner and healthier air
 High efficiency particle and gas filtration
 Odour removal during soldering
 Powerful blower maintains suction pressure throughout the filter's life
 High flow rate to collect all the smoke
 Quiet - lowest noise level on the market – less than 50dB
 Easy main and pre-filter change
 Low maintainance
 Easy-to-reach on/off switch
 ESD safe
 Retains Weller Easy-Click 60 Hose system

- ZeroSmog Guard Light, 120V,
 - 1 x main filter (HEPA H13 and Activated Carbon)
 - 5 x ePM1-75% prefilters
 - 1 x ALFA nozzle,
 - 1 x 0F15 Hose
 - 1 x Desk clamp

TECHNICAL DATA

Dimensions L x W x H	270 x 336 x 435 mm 10.63 x 13.23 x 17.13 in
ESD Safe	Yes
Maximum Capacity	100 (m³/h)
Maximum Vacuum	2700 Pa/V
Noise level (distance 1 m) dB(A)	less than 50 dBA
Power	60 W (100-120 V~)
UPC	037103378880
Voltage	100-120V (50/60 Hz)
Weight (Catalog)	9.5 kg
Product Family	Solder Fumes Volume Extraction 1-2 Workstations